



Two- or One-Diver Intercom

User's Guide



"Technology in Depth"

Undersea Systems International, Inc. dba Ocean Technology Systems

- NOTICE -

This manual and the information contained herein are provided for the use as a maintenance and operation guide. No license or rights to manufacture, preproduce, and/or sell either the manual or articles described herein are given. Undersea Systems International, Inc., *dba* Ocean Technology Systems, reserves the right to change specifications without notice. We recommend that all users read and fully understand this manual before using MK2-DCI.

All statements, technical information, and recommendations herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for intended use, and user assumes all risk and liability whatsoever in connection therewith. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage—direct, incidental, or consequential—arising from the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the Seller and Manufacturer.

- IMPORTANT SAFETY NOTICE - (Please read before using product.)

It is absolutely essential that all divers are properly trained and equipped and fully understand the owner's manual before attempting to use the Aquacom[®] MK2-DCI.

While Aquacom[®] MK2-DCI provides divers with good underwater communications, <u>it does not change or eliminate the potential hazards of diving!</u>

Do not attempt to charge batteries before reading the battery charging instructions in Section 4. Without following proper procedures, damage to the MK2-DCI, an explosion, and/or injury may occur.

Refer to the Library page of our Web site, www.otscomm.com, for a list of any changes made to this manual since its publication.

© Copyright 2024 by Undersea Systems International, Inc., dba **Ocean Technology Systems**. All rights reserved. Specifications are subject to change without prior notice.

TABLE OF CONTENTS

Section 1: Introduction1
Section 2: Specifications2
Section 3: Operating Instructions
3.1 System Components
3.2 Two-Wire Mode4
3.3 Four-Wire Mode5
Section 4: Batteries7
Section 5: Helpful Hints10
Limited Warranty13
Illustrations Figure 1. MK2-DCI Two-Diver Air Intercom Figure 2. Two-Wire Mode 6 Figure 3. Four-Wire Mode 6 Figure 4. Battery Setup 8 Figure 5. Battery PC Board

SECTION 1: INTRODUCTION

Congratulations! You have just purchased the finest, state-of-the-art hard-wire intercom in the world. Your new MK2-DCI Two- or One-Diver Air Intercom represents state-of-the-art technology and innovation—the choice of discriminating divers throughout the world. Please take the time to read this owner's manual. With proper care and use, your Ocean Technology Systems product will provide you with the ultimate in high-quality communications and reliability.

The MK2-DCI is a compact, self-contained Two- or One-Diver Air Intercom providing clear communications between the operator and diver(s). The MK2-DCI offers two- or four-wire communications.

This manual will cover specifications, operating instructions, two-wire or four-wire communications, batteries, helpful hints, and warranty information.

These guidelines and illustrations are presented to assist you. If you need additional information, do not hesitate to confer with your local OTS dealer or representative. If you require service, contact Ocean Technology Systems:

3133 West Harvard Street, Santa Ana, California 92704 USA	r
(800) 550-1984	
(714) 754-7848	
(714) 966-1639	
ots@otscomm.com	
http://www.otscomm.com	
	3133 West Harvard Street, Santa Ana, California 92704 USA (800) 550-1984 (714) 754-7848 (714) 966-1639 ots@otscomm.com http://www.otscomm.com

SECTION 2: SPECIFICATIONS

Battery Life:

Battery Type:

20 hours continuous use

Two 6-volt, 5.0 AH lantern batteries.

Recommended batteries:

Eveready Heavy-Duty Alkaline #528

Duracell Heavy-Duty Alkaline ID #9150. optional 6-volt rechargeable batteries.

WARNING: DO NOT USE A BATTERY THAT DOES NOT MEET THE LISTED SPECIFICATIONS.



Power Output:	20 watts		
Frequency Response:	600 to 12,000 Hz		
Cabinet Material:	ABS plastic		
Front Panel:	1/8" aluminum, chemically treated and coated with a tough, durable, urethane finish to withstand the marine environment.		
Size:	Height: 6-5/8" (16.8 cm) Width: 16-3/8" (41.6 cm) Depth: 8-3/8" (21.3 cm)		
Weight:	14.0 lbs.		

SECTION 3: OPERATING INSTRUCTIONS

3.1 SYSTEM COMPONENTS

See Figure 1 for a panel description.

1)	Record Out:	Permits tender to record diving operations (Line level). NOTE: DO NOT CONNECT PHANTOM POWER TO THE RECORD OUT JACK. DOING SO CAN DAMAGE YOUR UNIT.	
2)	Volume:	Tender-to-diver(s) volume control.	
3)	Power ON:	Turns the power ON or OFF.	
4)	Battery Level:	Color LEDs illuminate to alert tender to conditions of batteries.	
5)	Ext. Power:	A 12-volt, DC power source can be used.	
6)	Push-to-talk:	Push button used in two-wire mode by tender to talk to divers.	
7)	Tender Headset:	Tender-worn earphones connect via banana plug connectors.	
8)	Mic. (RED):	Used for hand-held or boom mic. via banana plug connector.	
9)	Volume:	Diver #1 diver-to-tender volume control.	
10)	Earphone:	Diver #1 earphone connection (banana or bare-wire style).	
11)	Microphone:	Diver #1 microphone connection (banana or bare-wire style).	
12)	Volume:	Diver #1 tender-to-diver volume control.	
13)	Microphone:	Diver #2 microphone connection (banana or bare-wire style).	
14)	Earphone:	Diver #2 microphone connection (banana or bare-wire style).	
15)	Handle:	Front panel handle (right & left side).	
16)	Volume:	Diver #2 tender-to-diver volume control.	
17)	Volume:	Diver #2 diver-to-tender volume control.	
18)	Speaker:	Front-panel speaker.	
19)	Thumb Screw:	One of four front panel screws (captive).	
20)	Speaker:	Remote speaker output (speaker level).	
21)	Volume:	Volume control for front panel speaker.	

- 22) **Speaker:** Switch to turn the front panel speaker ON or OFF.
- 23) **Cross Talk:** Switch used to cross-talk Diver 1 to Diver 2 or vice versa. Tender must hold the switch in the direction of the cross talk. This is a momentary switch.
- 24) **Diver Select:** Switch used to select Diver 1, Diver 2, or Both-Divers communications.

25) **REM:** This connector is used if a headset/boom microphone with a PTT switch is used.



Figure 1. MK2-DCI Two-Diver Air Intercom

3.2 TWO-WIRE MODE

In normal two-wire operations, the two wires within the diver communication cable are connected to the corresponding binding post (Divers #1 and #2) on the surface unit (Fig. 2). If a four-wire cable is used, two wires are normally twisted together for one side of the microphone binding post, and the remaining two wires twisted together for the other microphone binding post.

This configuration allows the tender to talk to the divers individually or both divers simultaneously. The diver(s) may also communicate with each other when the tender engages the cross-talk switch. The divers' speaker and the surface unit speaker both function as speaker and microphone. If required, a separate microphone and earphone can be used with the divers' masks or helmets. If a speaker is located in

a diving bell or recompression chamber, the MK2-DCI can be used as the communications link between the divers and the outside. When the system is used where conditions are noisy, the tender can switch off the speaker and use a headset and boom microphone. However, when using a headset with a boom microphone, the tender must use a push-to-talk (PTT) button to communicate. Our headset with a boom microphone has a PTT button located on one side of the headset. The MK2-DCI also has a PTT. The divers' communication is the primary signal. When the tender uses the PTT button, his signal becomes the primary signal. If the diver is trying to say something while the tender is talking, the tender will not hear the diver until he releases the PTT button.

The divers' helmets and/or full-face masks typically are wired with the earphones and microphones tied together. When wired like this, the divers' earphones and microphones function together. Bubbles passing by the earphones while the diver is talking will be picked up via the earphones, causing the communications to be noisy. When the tender is talking to the diver, his voice is heard not only from the diver's earphone, but also from the microphone!

3.3 FOUR-WIRE MODE

The four-wire mode provides continuous open-line communications between the tender and up to five divers, or any combination of recompression chambers or diving bells. The four-wire mode will give you optimum performance and intelligibility by the MK2-DCI. Using this method, everyone hears each other simultaneously. Therefore, the earphones, speakers, and microphones must be isolated to prevent feedback. All earphones are connected in parallel. A four-wire cable is required for all stations. Two of the wires are used for the microphone and two for the headset(s) and earphone(s) (Fig. 3). The diver earphones should be connected to the "EARPHONE" binding post on the surface unit (via the black banana plug located in the 1 or 2 Diver sections). The banana plug on the tender's OTS headset should be connected to the "EARPHONE" banana plug (black; Tender section). The remote plug on the headset should be connected to the "REM" receptacle located in the Tender section. The tender's microphone should be connected to the red banana plug labeled "MICROPHONE" (Tender's section). The diver's microphone should be connected to the "MICROPHONE" banana plug (red) in the Diver's setion of the MK2-DCI. When in the four-wire mode, everyone is on-line together. It is similar to a telephone conference call.

NOTE: The "Diver Select" must be in the "BOTH" position for four-wire communications in order to hear everyone. A headset with a boom microphone has to be used by the tender when using the MK2-DCI in the four-wire mode. If you experience feedback from the headset's microphone, turn off the front panel speaker.



SECTION 4: BATTERIES

The MK2-DCI Two-Diver Air Intercom can be powered by two 6-volt heavy duty alkaline batteries, rechargeable 6-volt batteries (Ocean Technology Systems' model no. RB-6), or a 12-volt alternate source. To recharge RB-6 batteries, obtain an RCS-13 universal smart charger from OTS or your local OTS dealer.

The following are options for the desired power source:

 <u>LANTERN BATTERIES</u>: The MK2-DCI is designed to use two 6-volt springconnector-type batteries. We recommend the use of 6-volt alkaline batteries, to achieve optimum performance. Eveready or Duracell alkaline batteries provide the best results for most diving operations. You can use standard 6-volt lantern batteries with spring connectors as well; however, battery life will be greatly reduced, and you will notice a substantial power drop when transmitting.

WARNING: DO NOT USE A BATTERY THAT DOES NOT MEET THE LISTED SPECIFICATIONS. BATTERY MUST BE A LANTERN TYPE AS SHOWN ON PAGE 2.

<u>INSTALLATION OF 6-VOLT BATTERIES</u>: Locate and loosen the four screws located on the front panel (Fig. 1, #19). These screws are captive and will not come off the front panel. Remove front panel from housing. Remove cotter pin from battery strap (Fig. 4, #3). Remove battery strap from battery housing (Fig. 4, #2). Insert both 6-volt, spring-type lantern batteries, springs facing toward battery PC board (Fig. 4, #4). Verify that the batteries are secure on the bottom of the housing and the backs are being held by the back plate. You will notice the batteries can be installed with springs in any direction on the PC board (Fig. 5). After batteries are installed, replace the battery strap and cotter pin, dress the wires so they are not pinched when you put the front panel back in place, replace the panel, and tighten the four screws (do not overtighten).

 <u>6-VOLT RECHARGEABLE BATTERY (RB-6V)</u>: When utilizing the optional RB-6V sealed lead acid battery, you will attain the maximum performance of a self-contained battery (two are required).

Install the RB-6V batteries per the instructions found in paragraph above #2, "INSTALLATION OF 6-VOLT BATTERIES."

The RCS-13 universal smart charger is available for rapid charging of RB-6 rechargeable batteries. It closely monitors the batteries' voltage level to charge them only as necessary. Power cords compatible with the electrical outlets of various regions of the world are available for use with the RCS-13.

To recharge the RB-6V batteries, you need not remove them from the MK2-DCI. Just connect the RCS-13 universal smart battery charger to the front-panel 12-volt external power jack. Then connect the charger's power plug to any



90-260–volt, 60-cycle power outlet. For further instructions and important information about charging with the RCS-13, refer to the instructions provided with the charger.

IMPORTANT SAFETY NOTE

Before you connect the battery charger to the external power jack, verify that the installed batteries are recharge-



able batteries. We recommend that rechargeable batteries be used when external power is supplied. The external source should provide a voltage greater than 12 but less than 15 volts. It will recharge the batteries while the system is operating.

Before powering up the MK2-DCI, always wait at least 20 minutes for any gasses expelled during charging to dissipate. While charging batteries, avoid smoking, open flames, or striking a match.

- 3) <u>ALTERNATE POWER SOURCE:</u> The external receptacle (Fig. 1, #5) provides an easy terminal for a marine or automotive 12-volt DC source. The power source should provide 12 volts and a minimum of 3 amps capacity. The alternate power source connection is also used for charging the battery.
- 4) <u>LOW-BATTERY LEDs</u>: The four LEDs illuminate one at a time, starting with the upper LED. Green represents fresh or fully charged batteries. As long as the

power is 11 volts or higher, the top green LED will illuminate. As the power decreases to approximately 10 volts, the second green LED will illuminate. The top green LED shuts off. When power falls to approximately 9 volts, the yellow LED will illuminate and the green LED will shut down. When power reaches approximately 8 volts, the red LED will illuminate and the yellow LED will shut down. At this point the MK2-DCI will audibly start warning you of lower seconds. When power falls below 8 volts, the red LED will start blinking and the warning beeps will come every 15 seconds.

At this point the MK2-DCI will audibly start warning you of lower power with a beeping sound every 30 seconds. When the voltage falls to about 7 volts, the red LED will start blinking and the warning beeps will come every 30 seconds. When the voltage falls below 7 volts, the beep occurs every 15 seconds. Below 6 volts the LED blinks quickly for a few seconds, after which the unit shuts off to save the battery from damage. The warning mode continues until the user installs fresh batteries, charges the batteries, or connects a 12-volt power source, or until the power drops enough to shut down the MK2-DCI (see the "LED Chart").

LED CHART				
COLOR	VOLTAGE	ON	BEEPING	
Green	11 volts DC or above	Solid	None	
Green	Approximately 10 volts	Solid	None	
Yellow	Approximately 9 volts	Solid	None	
Red	Approximately 8 volts	Solid	Every 30 seconds	
	Approximately 7 volts	Blinking	Every 30 seconds	
	Below 7 volts	Blinking	Every 15 seconds	

SECTION 5: HELPFUL HINTS

- 1) Before diving operations begin, check to be sure the microphone, earphones, and wire connections are secure and operating properly. Ninety percent of all problems in communications turn out to be a problem with one of the above.
- 2) When in the four-wire mode, you must use a headset with a boom microphone, and the Diver Select switch must be in the "BOTH" position. If feedback is present, switch off the front panel speaker (Fig. 1, #24).
- 3) Avoid excessive tender-to-diver volume. Most of the time, when there is too much volume, the diver will hear distortion and ask for more volume!
- 4) Before diving operations, always check the battery power level, and replace or recharge the batteries if necessary.
- 5) Make certain the headphone and remote PTT plugs are securely inserted into the proper receptacle.
- 6) When in the four-wire mode and a wire breaks, try setting the system up in the two-wire communication mode (Fig. 2), and continue diving operations.
- 7) Secure the MK2-DCI if using the unit on a vessel that is rolling about. Also strain-relief the umbilical(s) so they will not pull on the MK2-DCI.
- 8) Ensure the umbilicals are dressed out so as not to trip anyone.

TROUBLESHOOTING FOR MK2-DCI

PROBLEM	PROBABLE CAUSE	REMEDY
No Power	Battery exhausted	Replace battery
	Battery leads loose	Check battery connectors
	Defective ON/OFF switch	Change switch
	Board connector not making contact	Clean pins
	Open circuit on board	Repair or replace board
Power only for a short time when power switch is turned on	Defective boot circuit	Repair or replace board
	Defective CPU chip	Replace CPU or replace board
No diver voice	Loose connection at ribbon lead connector	Check connector; clean or reconnect
	Board connectors loose	Clean pins and reconnect
	Defective PCB	Replace board
	Defective speaker ON/OFF switch	Replace switch
	Defective volume controls	Replace control
	Defective panel speaker	Replace speaker
	Defective pre-amp chip	Replace
	Defective relay	Replace
	PTT logic circuits defective	Repair or replace board
No tender voice	Defective board	Replace
	Defective relay	Replace

PROBLEM	PROBABLE CAUSE	REMEDY
	Defective pre-amp chip	Replace
	Open trace on board	Repair trace or replace board
	PTT logic circuits defective	Repair or replace board
	Weak battery	Charge (if rechargeable) or replace
	Microphone pre-amp circuit defective	Trace signal to find fault and replace defective part
No record-out function	Board connector not making contact	Clean pins or replace defective connector
	Defective record amp	Trace fault around record op-amp and replace faulty part
		Replace board
Weak output to divers and tender	Power amplifier defective	Replace power amplifier chip
	Defective component that supports the power amplifier is defective	Trace part and replace
Distorted unintelligible speech	Bias supply faulty	Check supply and replace defective part
Cannot cross-talk divers	Defective cross-talk switch	Replace cross-talk switch
	Defective relays	Replace relays
	CPU defective	Replace CPU
Tender-to-diver faulty in two-wire mode	Defective PTT switch	Replace PTT switch
	Defective relays	Replace relays
	Defective CPU	Replace CPU

Undersea Systems International, Inc., *dba* Ocean Technology Systems

LIMITED WARRANTY

The MK2-DCI is fully warrantied against defects in materials and workmanship for a period of 1 year from the time of purchase. Our obligation under this warranty is limited to the replacing of any part or parts that prove to our satisfaction to have been defective and that have not been misused or carelessly handled. Labor is warantied for 1 year from time of purchase. The complete unit and/or part must be returned to our factory, transportation charges prepaid. We reserve the right to decline responsibility where repairs have been made or attempted by other than an Ocean Technology Systems factory-trained service center or properly trained personnel. In no event shall Ocean Technology Systems be liable for consequential damages.

You can now register your product online at the OTS Web site. Just visit http://www.otscomm.com/register1.html.

3133 West Harvard Street, Santa Ana, CA 92704, USA Telephone (714) 754-7848 • Toll-Free (800) 550-1984 • Fax (714) 966-1639 www.otscomm.com

© Copyright 2024 Undersea Systems International, Inc., dba Ocean Technology Systems All Rights Reserved. Specifications subject to change without prior notice.